



FEATURES

- 25mm Industry Tag is ATEX approved and thus can be used in potentially explosive atmosphere.
- The tag with multi read/write capability is very small in size and is made of ABS to meet all endurance requirements in terms of heat, harsh environments and chemical resistance.
- Perform in the harshest environments, including harsh chemicals, painting processes & outdoor exposure.
- Dust & Waterproof.
- Flexible Read/Write Range (reader dependant).
- Insensitive to almost all non metallic materials.

(25mm)



APPLICATIONS

- Being used in industrial environments, as well as in asset tracking applications
- It has been widely used in supply chain, service industries, distribution logistics and manufacturing companies to identify goods & objects in an industrial environment.
- Can be used to read through obstructions, including plastics, concrete and more.
- Suitable for factory floor manufacturing applications because of rugged construction (IP Rating).

Chip Type:	I-Code SLIX 13.56 MHz, ISO/IEC 15693	
	1024 bits, organized in 32 blocks of 4 bytes each	
	Data retention of 50 years	
	Write endurance 100,000 cycles	
Mechanical:	Outer Dia.	25mm
	Thickness	2.2mm
	Material	ABS
	Colour	Blue
	Weight	1.2 g
	Antenna Type	Wire Antenna
Electrical:	Operating Frequency	13.56 MHz
	Operating mode	Passive (battery-less transponder)
Ingress Protection:	IP67	
Thermal:	Storage Temp.	-20°C to +70°C
	Operating Temp.	-20°C to +70°C
Part Number:	204A1-Ex	
Atex Marking details:	Ex II 1 G, Ex ia IIC T5 Ga	
Options:	Other IC type, Size, Shape & Colour on request	
	Available with other plastic material e.g. PC/ABS	
*Desliminant Data Chart. Cartain an elfication publicat to about		

^{*}Preliminary Data Sheet: Certain specification subject to change.