



FEATURES

- The 34mm Tag with multi read/write capability is very small in size and perform best when is attached to metal.
- It is made of PA6 to meet all endurance requirements in terms of heat, harsh environments and chemical resistance.
- Perform in the harshest environments, including harsh chemicals, painting processes & outdoor exposure.
- Dust & Waterproof.
- Flexible Read/Write Range (reader dependant).

Industry Tag 34mm (Metal)

APPLICATIONS

- Specially tuned for metal application thus can be used in variety of applications having metallic environment.
- Being used in industrial environments, as well as in asset tracking applications
- It has been widely used in supply chain, service industries, distribution logistics and manufacturing companies to identify goods & objects in an industrial environment.
- Suitable for factory floor manufacturing applications because of rugged construction (IP Rating).

HitagS 256 bits 125KHz		
256 bits, organized in 8 blocks of 4 bytes each		
Data retention of 10 years		
Write endurance 100.000 cycles		
Outer Dia.	34mm	
Hole Dia.	5.6mm	
Thickness	8mm	
Material	Polyamide	
Colour	black	
Weight	8 g	
Operating Frequency	125 KHz	
Operating mode	Passive (battery-less transponder)	
IP68		
Storage Temp.	-40°C to +85°C	
Operating Temp.	-25°C to +85°C	
146N1		
Other IC type, Size, Shape & Co	ner IC type, Size, Shape & Colour on request	
Available with other plastic material e.g. PC/ABS		
	256 bits, organized in 8 blocks Data retention of 10 years Write endurance 100.000 cycle Outer Dia. Hole Dia. Thickness Material Colour Weight Operating Frequency Operating mode IP68 Storage Temp. Operating Temp.	

*Preliminary Data Sheet: Certain specification subject to change.