

Ultra-Rugged UHF RFID Tag

UHF RFID Tag WT-A533/WT-A533HT

Wash, Rinse,
Track, Repeat.

Ultra-Rugged UHF RFID Tags for Commercial and Industrial Textile Applications

- ▶ UHF technology to read hundreds of tags simultaneously
- ▶ More than 8 foot reading distance
- ▶ New mechanical design for improved performance for flat linens
- ▶ Cost efficient solution with exceptional durability for washing, drying, dry cleaning and ironing
- ▶ Suitable for high-pressure extractors up to 60 bar
- ▶ Suitable for Autoclave sterilization
- ▶ Small, soft, flexible material ideal for textiles, linens, garments and accessories
- ▶ Conforms to "ISO/IEC 18000-63 (formerly 18000-6C) and EPC Gen2"
- ▶ 100% non-magnetic construction, suitable for hospital use



The Fujitsu logo, consisting of the word "FUJITSU" in a bold, red, sans-serif font, with a stylized infinity symbol above the letter "J".

Wash, Rinse,
Track, Repeat.

UHF RFID Tag

WT-A533/WT-A533HT

Fujitsu's Industrial RFID Flexible Linen Tags

Fujitsu latest industrial strength flexible UHF RFID tags have a new mechanical design offering improved performance for flat linen processing using high pressure extractors and flatwork ironers. Fujitsu tags enable bulk reading of hundreds of items simultaneously with the extended range and accuracy of state-of-the-art UHF tag technology. Laundries will greatly improve linen and garment processing with near 100% accurate reading and enhanced both soiled and clean items. Garment and Linen owners will see improved asset tracking and reduced loss, while keep their costs low by improving workflow and efficiency.

Advantages of UHF Technology

Speed

UHF efficiency increases tag read performance to read hundreds of tags in a single pass.

Rugged

Can withstand high pressure extractors and flatworks irons used in high-throughput laundries

Accuracy

Inventory management can be performed accurately and easily by reading multiple tags with very low error rates.

ROI

Installation of UHF technology will provide cost-effective garment management by reducing labor cost associated with barcode or high frequency RFID tags.



| Specifications | | | |
|-------------------------------|--|--|--|
| Model | | Fujitsu RFID Tag WT-A533 | |
| RFID Standard | | ISO/IEC 18000-63 (EPC Gen2) | |
| Size & Weight | | 55(W) x 10 (D) x 1.6 (H) mm, 1.05g | |
| EPC Number Area | | 128bit (The first 96bit are pre-written by Fujitsu) | |
| User Memory | | NONE | |
| Reading Range | Textile | 902-928MHz | 4W eirp: 250 cm |
| | | 865.6-867.7 MHz | 2W erp: 200 cm |
| | Rubber Mat | 902-928MHz | 4W eirp: 200 cm |
| | | 865.6-867.7 MHz | 2W erp: 200 cm |
| Tagging | | Sewing, Heat-sealing, Pouch | |
| Estimated Lifetime | | 200 washing cycles/dry cleaning or 3 years from shipping date, whichever comes first ^{*1} | |
| Estimated Annual Failure Rate | | Less than 0.5% excluding DOA (Excludes discoloration, bending, distortion, etc. due to normal use) | |
| Environmental Resistance | Washing Method | | Laundry, Dry cleaning ^{*2} (Perchloroethylene, Hydrocarbon solvent) |
| | WaterExtraction Pressure | | 60 bar ^{*3} |
| | Water Resistance | | Water resistant |
| | Chemical Resistance | | Detergent, Softener, Bleach (Oxygen/ Chlorine), Alkali ^{*4} |
| | Autoclave Heat Sterilization | | 121C, 15-20 minutes ^{*5} |
| | Heat Resistance | Drying | 85 °C (Up to 60min.) or 120 °C (Up to 10 min.) |
| | | Ironing | 200 °C (Up to 10 sec. with press cloth) |
| | Temperature/Humidity Operating/Storage | | -20 to 50 °C, 10 to 95% RH |
| -40 to 55 °C, 8 to 95% RH | | | |

All data are results performed in our test condition according to Japan Industrial Standard JIS L 0217 - 102, 301, 401, 402. Your test result may vary.

*1: Nominal industrial laundry conditions, 40 bar water extraction pressure

*2: Conditions for dry cleaning: Up to 10min./cycle (Washing), More than 30min./cycle within 60 °C (Drying)

*3: Tested in Fujitsu Frontech Laundry testing condition: 100 cycles at 60 bar with a simulated extractor press.

*4: The tag has been tested for 10 times at the condition of JIS L 0856 Severe test.

*5: 80 cycles or more depending on chamber conditions

*6: Fujitsu provides no warranty nor maintains liability for failure due to laundry or dry-cleaning chemicals not verified.



Fujitsu Frontech North America, Inc.
<http://www.fujitsufrontechna.com>
27121 Towne Centre Drive, #100 Foothill Ranch, CA. 92610

©Copyright 2016 Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify at any time without notice these statements, our services, products, and their warranty and performance specifications.

