

MARS

Multi Antenna Reader System



Overview

The Multiple Antenna Reader System (**MARS**) is an RFID reader/writer designed to meet the requirements to verify, inventory, monitor and control a large number of valuable items located in one position or moving on a conveyor at high speed.

The **MARS** is a high performance system for PJM StackTag® and PJM ItemTag® RFID tags. It provides fast and reliable operations with multiple antennas.

Product Description

The **MARS** operates with external antennas which can be installed for specific applications. It comes in four versions:


- MARS-1: single antenna
- MARS-2: up to 2 antennas
- MARS-4: up to 4 antennas
- MARS-6: I/O port, up to 6 antennas

The **MARS** is particularly well suited for applications in

- gaming
- jewelry
- document management
- pharmaceutical sectors
- retail

The **MARS** features:

- The ability to identify, read and write reliably to up to 150 tags per second
- Reliable identification of tightly stacked, overlapping or touching tags
- Fast operation with 2 reply channels
- Operates PJM StackTag® and PJM ItemTag® simultaneously
- A powerful processing platform allowing for stand-alone reader operation
- Very good connectivity offering both Ethernet and USB interfaces
- General purpose digital I/O (MARS-6)
- Complies with ISO/IEC 18000-3 Mode 2



Specifications

- Read and write operations
- No user-serviceable parts
- ISO/IEC Compliance: 18000-3 Mode 2
- Operating frequency 13.56 MHz
- Certified for FCC, CE, CSA/UL, Canadian and Australian standards
- External dimensions (L x W x H):
310 x 213 x 46 mm incl. fixed mounting brackets
- Net weight: 1.5 kg (without external antennas)

- Low voltage input: 12 VDC @ 2.5 A
- Operation environment: Indoor use
- Temperature range: +10°C to +45°C
- Humidity: 10% to 80% (non-condensing)
- Minimum host computer requirements:
Windows XP SP2/ 500 MHz CPU/ 128MB RAM
- Host interface: USB and Ethernet



- Command data rate of 424 kbit/s
- Reply data rate of 106 kbit/s per channel
- Number of reply channels: 2
- Number of external antennas: 1, 2, 4 or 6
- Antenna connection cable of 1.5 m length
- Single axis antennas with dimensions:
Round: 60 mm dia. and 124 mm dia.
Rectangular: 60 x 420 mm, 120 x 240 mm
and 202 x 352 mm
(special antennas are available on request)



For further information on technology, delivery terms and conditions and prices please contact your nearest Magellan Technology office:

Magellan Technology Pty Ltd
65 Johnston Street
Annandale NSW 2038
Australia
Phone: +61 2 9562 9800
Fax: +61 2 9518 7620
info@magellan-technology.com

Magellan Technology Europe Ltd.
Units 7 & 8
Parker Court, Dyson Way
Staffordshire Technology Park,
Beaconsfield
Stafford ST18 0WP
UK
Phone: +44 1785 218540
Fax: +44 1785 218541
info@magellan-rfid.com

About Magellan

Magellan Technology Pty Ltd, Sydney, Australia, is a technology developer, manufacturer and licensor of advanced read/write 13.56 MHz RFID systems. Magellan designs and offers RFID chips, inlets, a complete portfolio of reader/writers and operating software. Magellan's Phase Jitter Modulation (PJM) technology complies with the International Standard ISO/IEC 18000 Part 3 Mode 2.