

POS-PODIUM PRODUCT SPECIFICATIONS



2111 MODEL



Dimensions: (width x depth x height) Height with feet:

21.25 x 11.1 x 3.4 inches 540 x 282 x 87 mm 3.9 inches or 92 mm

Shipping weight:

22 lbs 10.0 kg

FEATURES

- Uniquely designed to be mounted above the scanner at the point of sale
- Configurations available for placement downstream from the scanner
- Dual media slots standard
- Tested to last beyond 2 million operations

- Heavy duty steel ball bearing slides •
- Available in Black and Cloud White, with either a painted or stainless steel drawer front
- Four function lock
- Closed and latched drawer status switch
- Random keying is standard, other lock and key options available

AVAILABLE INTERFACES

- MultiPRO[®] 24 volt * 320
- MultiPRO[®] II 12 volt * 420
- MultiPRO[®] III Dual 12/24 volt * 520

XXX Other numbers indicate the DirectPRO® hardwired or a custom interface

* Requires detachable cable sold separately. Refer to Connectivity Guide at www.apgcashdrawer.com for interface cable detail.

OPERATING ENVIRONMENT

Storage Temperature

-30°C to +50°C (-22°F to +122°F)

Operating Temperature

0°C to +40°C (+32°F to +104°F)

Relative Humidity (non-condensing)

TILL -

- Uniquely designed till offers 5 bill, 6 coin storage
- Locking till cover available
- · All measurements shown as width x depth x height

PK-15TA-07-BX 5 bill. 6 coin Fixed bill/coin widths 19 x 9.87 x 2 inch 482 x 250 x 51 mm



APG[®] Cash Drawer, the APG Cash Drawer logo,

ParallelPRO[™], POS–Integrator[™], Vasario[™],

POS–Podium[™] and Cash Drawer Caddy[™] are trademarks of APG Cash Drawer, LLC.

SerialPRO[®], MultiPRO[®], DirectPRO[®], USBPro[™],

10% to 95%

WARRANTY

Two (2) year limited warranty. A full warranty statement is available online at www.apgcashdrawer.com/support/warranty-statement.



APG Cash Drawer, LLC 5250 Industrial Blvd. N.E. Minneapolis, MN 55421

763 571 5000 763 571 5771

Fax: Visit us on the web at www.apgcashdrawer.com

Phone:

© 2010 APG Cash Drawer, LLC

M-43-110 Rev. B